



Type 1

# EV Meter Pay

**A smart level-2 public charging station designed for hotels, shopping centers, parking lots, workplaces, municipalities and more.**

This universal charging station is equipped with a built-in card reader that accepts every payment method including debit and credit cards, digital wallets, QR codes, prepaid, NFC and more. EV Meter's smart, secure and feature-rich solution enables businesses to take initiative and maximize their revenue.



## 24/7 Monitoring

Real-time event notifications and remote software updates



## Easy Installation

Quick to deploy in any location



## Weather Resistant

Designed to withstand any environmental conditions



## Open Payment System

Accept any type of payment method



## OCPP Supported

Manage the charging station by using EV Meter Core or any other management platform



## Multi-Language

Operates in 15 languages with unique voice interaction features



# EV Meter Pay



Electrical Data	AC Power Supply	L1 + L2/N + PE
	AC Input Voltage	110-240 VAC +/- 10%, 50-60Hz
	AC Output Voltage	110-240 VAC +/- 10%, 50-60Hz
	Maximum Input / Output Current	50A max
	Maximum Input / Output Power	12kW
	Number of Plugs	One
Communication	Interface Protocol Server Communication	OCPP 1.6 Supported Ethernet, 4G
Supported Payment Schemes	Debit & Credit Cards Mobile & NFC Payments	Swipe, contact, contactless, EMV chip cards
	Prepaid cards & closed environments Static and Dynamic QR codes	
Safety & Protections	Safety Protections	Electronic RCD 30mA AC Electronic 6mA DC Fault current detection
	Power Limit Control	Mode 3 PWM control according to UL-2594
	Type 1 Socket Protection	J-1772 Type 1 connector
	Available Connections	Type 1 Plug, 16.4 ft cable
Enclosure & Environmental Conditions	IP Rating	IP55
	Enclosure Impact Protection	IK8
	Payment Terminal Impact Protection	IK8
	Enclosure Material	PC + UV
	Operating Temperature	131 °F to 122 °F
	Ambient Temperature Storage	-22 °F to 158 °F
	Status LEDs	Yes
	Light Beacon	RGB color indicator
	Built-in Energy Meter	Yes
Weight & Dimensions (WxHxD)	18*12*7 in, 17.6 lbs	
Standards & Certifications	FCC	
	ROHS	
	REACH	