

Bee Meter VPOS Touch

A smart level-2 public charging station designated for hotels, shopping centers, parking lots, workplaces, municipalities and more.

This universal charging station is equipped with a built-in card reader that accepts every payment method including debit and credit cards, digital wallets, QR codes, prepaid, NFC and more. EV Meter's smart, secure and feature-rich solution enables businesses to take initiative and maximize their revenue.



24/7 Monitoring

Real-time event notifications and remote software updates



Easy Installation

Quick to deploy in any location



Weather Resistant

Designed to withstand any environmental conditions



Open Payment System

Accept any type of payment method



OCPP Supported

Manage the charging station by using HIVE or any other management platform



Multi-Language

Operates in 15 languages with unique voice interaction features



Bee Meter Vpos Touch



Electrical Data	AC Power Supply	3P + N + PE
	AC Input Voltage	380-400 VAC +/-10%, 50-60Hz
	AC Output Voltage	380-400 VAC +/-10%, 50-60Hz
	Maximum Input / Output Current	3x32A
	Maximum Input / Output Power	22kW
	Number of Plugs	One
Communication	Interface Protocol	OCPP 1.6 Supported
	Server Communication	Ethernet, 4G
Supported Payment Schemes	Debit & Credit Cards	Swipe, contact, contactless, EMV chip cards
	Mobile & NFC Payments	Google Pay, Apple Pay, Swish and more
	Prepaid cards & closed environments	Alipay, WeChat Pay and others
	Static and Dynamic QR codes	
Safety & Protections	Safety Protections	Electronic RCD 30mA AC Electronic 6mA DC Fault current detection
	Power Limit Control	Mode 3 PWM control according to IEC 61851-1
	Type 2 Socket Protection	IEC 62196-1, IEC 62196-2
	Available Connections	Type 2 Socket or 5m Cable with Plug
Enclosure & Environmental Conditions	IP Rating	IP55
	Enclosure Material	PC + UV
	Operating Temperature	(-25°C) to (+55°C)
	Ambient Temperature Storage	(-30°C) to (+70°C)
	Status LEDs	Yes
	Light Beacon	RGB color indicator
	Built-in Energy Meter	Yes
Weight & Dimensions (WxHxD)	Cable	450x300x180 mm, 8Kg
	Socket	480x300x180 mm, 6Kg
Standards & Certifications	ROHS	
	REACH	
	CE Compliant	
Optional Devices	Type 2 Socket Protection	Shutter
	Dynamic Load Management	Yes
	Pedestal	Yes